



ARMAZÓN BASE



PLACA CALENTADORA / REFRENTADOR



UNIDAD ELECTRO HIDRÁULICA



GAMA DE DN160 a DN1200

ARMAZÓN BASE	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Gama de medidas	50-160	75-250	90-315	160-400	250-500	355-630	630-800	710-1200
Dimensiones exteriores (cm)	79x39x41	79x44x47	79x55x54		121x66x70			
Peso sin suplementos (kg)	32,5	41	44,5	71	107	250	320	380
Juego de suplementos básicos	90, 110, 125	110, 125, 160, 180, 200	200, 225, 250	250, 280, 315, 355	355, 400, 450	400, 450, 560	630, 710	710, 800, 900, 1000
Dimensiones caja transporte (cm)	54x36x12	64x35x17	64x35x17		76x44x36			
Peso suplementos (kg) (con caja)	10	24	18,5	55	68	260	200	680

PLACA CALENTADORA	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Voltaje (Vac)			230				400	
Potencia (W)	1000	1900	2100	3100	3800	6800	8000	16000
Regulación de la temperatura	Electrónica Ajustable de 180 a 280 °C							
Revestimiento	PTFE							
Dimensiones exteriores (cm)	27x6,5x50	36x12x58	47x11x70		64x8x110			
Peso (kg)	3,35	5,5	7,2	9	17,5	30	30	120

REFRENTADOR	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Voltaje (Vac)			230				400	
Potencia (W)	500	1010	1010	1010	750	1100	1100	1500
Cuchillas de corte	Ajustables de doble filo							
Dimensiones exteriores (cm)	36x26x45	41x36x42	46x47x55		62x23x98			
Peso (kg)	8,3	15,3	21,8	31	58	70	120	180

SOPORTE PLACA+REFRENTADOR	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Dimensiones Exteriores (cm)	32x25,5x34	36x33x34	40x37x42		60x60x70			
Peso (kg)	4,22	6,5	8		22,5			

UNIDAD ELECTRO HIDRÁULICA	TRACK 160 - 250	TRACK 315 - 400	TRACK 500	TRACK 630 - 800	TRACK 1200
Voltaje (Vac)	230 (monofásico)			400 (trifásico)	
Potencia (Kw)	0,37	0,55	0,75	0,75	1,1
Presión máxima (bar)	55	95	150	150	150
Manómetro (bar)	0-60	0-100	0-160	0-160	0-160
Dimensiones exteriores (cm)	51x31x41,5	51x31x41,5	51x31x41,5		
Peso (kg)	26,5	29,6	31,5	70	70

MÁQUINA COMPLETA	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Voltaje (Vac)	230 (monofásico)				400 (trifásico)			
Potencia (Kw)	1,87	3,28	3,66	4,86	6,75	8,65	10,2	18,6
Peso neto sin suplementos(kg)	75	95	111		236,5			
Peso neto con suplementos (kg)	87	119	137		304,5			

ESPECIFICACIONES GRUPO GENERADOR	TRACK 160	TRACK 250	TRACK 315	TRACK 400	TRACK 500	TRACK 630	TRACK 800	TRACK 1200
Voltaje (Vac)	230 (monofásico)				400 (trifásico)			
Potencia mínima aconsejable (VA)	2500	4000	4500	6000	8500	10800	13000	24000